



# TAURUS POINT HP

- ✓ New tread pattern
  - Longevity and comfort on the road
  - Optimal traction and self-cleaning capacity
- ✓ Robust casing
  - For a longer service life

## SIZES

600/65 R28 154A8/154B TL
600/70 R30 158A8/158B TL
710/70 R38 171A8/171B TL
650/85 R38 173A8/173B TL
710/70 R42 173D TL

# TAURUS POINT HP

Tyre specifications and pressure table (bar & psi). Load per tyre in kg\*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
<b>28</b>	<b>600/65 R28 154A8/154B TL</b>	084072	591	1491	746	4402	DW20B (A)		DW18 DW18L	717	405	48		
<b>Bar</b>	<b>0.8 1.0 1.2 1.4 1.6 1.8 2.0 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8</b>													
<b>Psi</b>	<b>12 15 17 20 23 26 29 30 32 33 35 36 38 39 41</b>													
10 km/h **	2990 3360 3690 4020 4350 4565 4775 4880 4990 5095 5200 5305 5415 5520 5625													
30 km/h	2220 2525 2805 3090 3370 3530 3695 3775 3855 3935 4015													
40 km/h	2055 2360 2625 2885 3150 3300 3450 3525 3600 3675 3750													
50 km/h	2360 2625 2885 3150 3300 3450 3525 3600 3675 3750													
40 km/h Dual	1810 2075 2305 2540 2770 2905 3035 3100 3170 3235 3300													

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
<b>30</b>	<b>600/65 R30 158A8/158B TL</b>	424355	591	1602	700	4730	DW20B (A)		DW18L	737	450	50		
<b>Bar</b>	<b>0.8 1.0 1.2 1.4 1.6 1.8 2.0 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8</b>													
<b>Psi</b>	<b>12 15 17 20 23 26 29 30 32 33 35 36 38 39 41</b>													
10 km/h **	3325 3750 4175 4600 5025 5250 5475 5590 5700 5815 5925 6040 6150 6265 6375													
30 km/h	2480 2835 3190 3550 3905 4065 4230 4310 4390 4470 4550													
40 km/h	2325 2650 2985 3315 3650 3800 3950 4025 4100 4175 4250													
50 km/h	2325 2650 2985 3315 3650 3800 3950 4025 4100 4175 4250													
40 km/h Dual	2045 2330 2625 2915 3210 3345 3475 3540 3610 3675 3740													

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
<b>38</b>	<b>710/70 R38 171A8/171B TL</b>	381004	719	1969	860	5838	DW23B (A)		DW25B (A) MW23B (A) MW25B (A)	804	811	55		
<b>Bar</b>	<b>0.8 1.0 1.2 1.4 1.6 1.8 2.0 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8</b>													
<b>Psi</b>	<b>12 15 17 20 23 26 29 30 32 33 35 36 38 39 41</b>													
10 km/h **	4865 5475 6090 6700 7315 7635 7950 8110 8270 8430 8590 8750 8905 9065 9225													
30 km/h	3630 4145 4655 5160 5670 5900 6125 6240 6355 6465 6580													
40 km/h	3390 3875 4350 4825 5300 5515 5725 5830 5940 6045 6150													
50 km/h	3390 3875 4350 4825 5300 5515 5725 5830 5940 6045 6150													
40 km/h Dual	2985 3410 3830 4245 4665 4850 5040 5130 5225 5315 5410													

\* Refer to the notes at the end of the tables of this range

# TAURUS POINT HP

Tyre specifications and pressure table (bar & psi). Load per tyre in kg\*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>38</b>	<b>650/85 R38 173A8/173B TL</b>	192125	696	2066	903	6135	DW23B (A)		DW20B (A) MW23B (A)	804	857	56
<b>Bar</b>	<b>0.8 1.0 1.2 1.4 1.6 1.8 2.0 2.1 2.2 2.3 2.4</b>	<b>1.4 1.6 1.8 2.0 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8</b>										
<b>Psi</b>	<b>12 15 17 20 23 26 29 30 32 33 35</b>	<b>20 23 26 29 30 32 33 35 36 38 39 41</b>										
10 km/h **	5000 5625 6250 6875 7500 7875 8250 8440 8625 8815 9000 9190 9375 9565 9750											
30 km/h	3745 4280 4795 5315 5830 6110 6395 6535 6675 6815 6955											
40 km/h	3500 4000 4485 4965 5450 5715 5975 6105 6240 6370 6500											
50 km/h	3500 4000 4485 4965 5450 5715 5975 6105 6240 6370 6500											
40 km/h Dual	3080 3520 3945 4370 4795 5025 5260 5375 5490 5605 5720											

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>42</b>	<b>710/70 R42 173D TL</b>	402666	716	2082	933	6181	DW23B (A)		DW25B (A) MW23B (A)   MW25B (A)	802	872	59
<b>Bar</b>	<b>0.8 1.0 1.2 1.4 1.6 1.8 2.0 2.1 2.2 2.3 2.4</b>	<b>1.4 1.6 1.8 2.0 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8</b>										
<b>Psi</b>	<b>12 15 17 20 23 26 29 30 32 33 35</b>	<b>20 23 26 29 30 32 33 35 36 38 39 41</b>										
10 km/h **	4800 5325 6000 6675 7350 8025 8700 8830 8965 9095 9225 9355 9490 9620 9750											
30 km/h	4065 4660 5250 5845 6440 6700 6960 7085 7215 7345 7475											
40 km/h	3855 4425 4990 5560 6130 6380 6625 6750 6875 6995 7120											
50 km/h	3695 4240 4790 5335 5880 6115 6355 6470 6590 6705 6825											
65 km/h	4000 4535 5065 5600 5825 6050 6165 6275 6390 6500											
40 km/h Dual	3405 3905 4400 4900 5395 5615 5830 5940 6050 6155 6265											

#### \*IMPORTANT:

The inflation pressure must always be appropriate for the load per TYRE, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (July 2019). Technical data is subject to change without prior notice.

- For plowing and other field applications subject to high torque, use the 30 km/h line.
  - When using single TYRE configuration:
    - add 0.4 bar for use on slopes of more than 20%
    - add 0.4 bar for intensive road use exceeding 50%
- \*\*10 km/h LT (Low Torque) (max speed 10 km/h).